

White
length: 2 m

fully assembled DLP trunking 50 x 150

trunking and fittings



Selection chart (p. 706)
Wiring capacity chart (p. 726)

Conform to NF C 68-104

| Pack | Cat.Nos | Fully assembled trunking |
|-------------------|---------|--|
| 12 ⁽¹⁾ | 104 27 | Trunking with partition Supplied with: – one 50 x 150 mm body – two flexible cover 65 mm wide Fits onto the whole trunking including in internal and external angles Suitable for an optimized installation with Mosaic wiring accessories by the use of Mosaic sockets with support Length 2 m |
| 24 ⁽¹⁾ | 105 82 | Separation partition Length 2 m |
| 20 | 106 91 | Joints Body joint For aligning bases during installation |
| 20 | 106 92 | Body joint, attached with adhesive (fit at the end of installation) |
| 10 | 108 01 | Cover joint for 65 mm cover |

| Pack | Cat.Nos | Junctions |
|------|---------|---|
| 5 | 107 35 | Flat junctions For tap-off to a 80 mm wide branch |
| 5 | 107 37 | For tap-off to a 105 mm wide branch equipped with a 65 mm cover |
| 5 | 107 36 | For tap-off to a 105 mm wide branch equipped with a 85 mm cover |
| 5 | 107 63 | Angled junction For tap-off in an internal angle to 35 x 80, 35 x 105, 50 x 80, 50 x 105 For use with internal angle Cat.No 106 06 |

| Pack | Cat.Nos | Accessories |
|------|---------|----------------|
| 50 | 106 81 | Clip |
| 100 | 308 81 | Base for clamp |

| Pack | Cat.Nos | Angles and end cap |
|------|---------|---|
| 5 | 106 06 | Internal and external angles Include the 3 components making the angle (parts for the top and bottom and the partition junction) on which the flexible cover is fitted Changeable internal angle, from 85° to 95° for 50 x 150 and 50 x 195 mm trunkings |
| 5 | 106 35 | Changeable external angle, from 60° to 120° for 50 x 150 and 50 x 195 mm trunkings |
| 5 | 107 89 | Flat angle 90° flat angle |
| 10 | 107 03 | End cap Left or right end cap |

Installation accessories (p. 724)

Other functions

see p. 724

(1) Number of meters in pack